

HEX HEADS AND HEX WASHER HEADS FOR MACHINE SCREWS												ASME B18.6.3-2002	
Nominal Size	A Width Across Flats		W Width Across Corners	H Height of Head		F Diameter of Washer		U Thickness of Washer		J Width of Slot		T Depth of Slot	
	2	.125	.120	.134	.050	.040	.166	.154	.016	.010	-	-	-
4	.188	.181	.202	.060	.049	.243	.225	.019	.011	.039	.031	.042	.025
5	.188	.181	.202	.070	.058	.260	.240	.025	.015	.043	.035	.049	.030
6	.250	.244	.272	.093	.080	.328	.302	.025	.015	.048	.039	.053	.033
8	.250	.244	.272	.110	.096	.348	.322	.031	.019	.054	.045	.074	.052
10	.312	. <mark>3</mark> 05	.340	.120	.105	.414	.384	.031	.019	.060	.050	.080	.057
12	.312	.305	.340	.155	.139	.432	.398	.039	.022	.067	.056	.103	.077
1/4	.375	. <mark>3</mark> 67	.409	.190	.172	.520	.480	.050	.030	. <mark>075</mark>	.064	.111	.083
5/16	.500	.489	.545	.230	.208	.676	.624	.055	.035	.084	.072	.134	.100
3/8	.562	. <mark>5</mark> 51	.614	.295	.270	.780	.720	.063	.037	.094	.081	.168	.131
1/2	.750	.735	.820	.400	.367	1.040	.960	.085	.050	-	-	-	-