

## TINNERMAN® NUT ALTERNATIVES



## STEEL SPRING NUTS FLAT TYPE

Tinnerman®\*, SAE  
J891

Industry Part Number	Screw Size	L	W	T	PERFORMANCE DATA	
		Length	Width	Material Thickness	Recommended Installation Torque (lb.-in.)	Ultimate Tensile Strength (lb.)
					Max	Min
C105SS-440-4	4/40	.44	.25	.012	3	100
C430-1032-4	10/32	.75	.44	.017	-	-
C7000-4-4	4A or B	.38	.25	.022	9	300
C7000-632-4	6/32	.44	.28	.017	6	156
C7000-6-4	6A or B	.50	.31	.025	12	425
C7000-832-4	8/32	.50	.31	.017	8	189
C7000-8-4	8A or B	.63	.41	.028	20	534
C7000-1024-4	10/24	.63	.38	.022	14	274
C7000-10-4	10A or B	.75	.50	.031	35	672
C7000-1420	1/4-20	.75	.50	.025	35	570

<b>Description</b>	A one piece, self-locking fastener made of spring steel. The perimeter of the nut is rectangular in shape. Some variations have an arched base and/or corners which are trimmed or turned.
<b>Applications/ Advantages</b>	It reduces inventories by eliminating need for lockwashers and spanners. Its single thread engagement design makes it easy to apply and remove. Parts are reusable. Provides the correct amount of spring tension without damaging enamel, glass or porcelain surfaces.
<b>Material</b>	SAE 1050 or higher carbon steel, with the exception of part# C105SS-440-4 which is made of stainless steel.
<b>Hardness (Steel)</b>	For material thickness 0.017-0.024 in., Rockwell 30N C40 minimum, C50 maximum. For material thickness 0.025-0.039 in., Rockwell 45N C40 minimum, C50 maximum.
<b>Plating</b>	See Appendix-A for information on the plating of steel spring nuts.

Tinnerman® is a registered trademark of Trans Technology Engineered Components, LLC, Eaton Yale & Towne Inc.. Our spring nuts are not manufactured by or connected with the producers of Tinnerman® nuts.