




## TINNERMAN® NUT ALTERNATIVES



### STEEL SPRING NUTS "J" TYPE

Tinnerman® &  
SAE J891

Industry Part Number	Screw Size	P	L	W	D	T	PERFORMANCE DATA	
		Panel Range	Length	Width	Distance Center of Hole to Edge Max	Material Thickness	Recommended Installation Torque (lb.-in.) Max	Ultimate Tensile Strength (lb.) Min
C8019-632-4	6/32	.025-.040	.47	.50	.218	.017	6	156
C8020-632-4	6/32	.045-.062	.47	.50	.218	.017	6	156
C8022-632-4	6/32	.045-.062	.63	.31	.296	.017	6	156
C8023-632-4	6/32	.025-.040	.81	.31	.468	.017	6	156
C8024-632-4	6/32	.045-.062	.81	.31	.468	.017	6	156
C8025-6-4	6A or B	.025-.040	.47	.50	.218	.025	12	425
C8026-6-4	6A or B	.045-.062	.47	.50	.218	.025	12	425
C8029-6-4	6A or B	.025-.040	.81	.31	.468	.025	12	425
C8030-6-4	6A or B	.045-.062	.81	.31	.468	.025	12	425
C8031-832-4	8/32	.025-.040	.53	.50	.234	.017	8	189
C8032-832-4	8/32	.045-.062	.52	.50	.234	.017	8	189
C8035-832-4	8/32	.025-.040	.87	.41	.514	.017	8	189
C8036-832-4	8/32	.045-.062	.87	.41	.514	.017	8	189
C8037-8-4	8A or B	.025-.045	.53	.50	.234	.028	20	534
C8038-8-4	8A or B	.045-.062	.53	.50	.234	.028	20	534
C8041-8-4	8A or B	.025-.040	.87	.41	.515	.028	20	534
C8042-8-4	8A or B	.045-.062	.86	.41	.515	.028	20	534
C8043-1024-4	10/24	.025-.040	.59	.63	.203	.022	14	274
C8044-1024-4	10/24	.045-.062	.59	.63	.203	.022	14	274
C8045-1024-4	10/24	.025-.040	.79	.38	.359	.022	14	274
C8047-1024-4	10/24	.025-.040	.97	.35	.562	.022	14	274
C8048-1024-4	10/24	.045-.062	.97	.38	.562	.022	14	274
C8043-1032-4	10/32	.025-.040	.59	.63	.203	.017	-	-
C8049-10-4	10A or B	.025-.040	.58	.63	.250	.031	35	672
C8050-10-4	10A or B	.045-.062	.58	.63	.250	.031	35	672
C8053-10-4	10A or B	.025-.040	.97	.50	.562	.031	35	672
C8054-10-4	10A or B	.045-.062	.97	.50	.562	.031	35	672
C7740-1420-4	1/4-20	.075-.094	1.10	.625	.687	.025	35	570

<b>Description</b>	A self-retaining spring steel fastener manufactured in the shape of a "J", enabling it to snap into place over the edge of a panel and hold its position.
<b>Applications/Advantages</b>	Same advantages as a flat-type spring nut, but more versatile. Can reduce assembly time by eliminating such steps as welding and riveting. Nut surface will accept paint without clogging inside the thread.
<b>Material</b>	SAE 1050 or higher carbon steel.
<b>Hardness</b>	For material thickness 0.017-0.024 in., Rockwell 30N C40 minimum, C50 maximum. For material thickness 0.025-0.039 in., Rockwell 45N C40 minimum, C50 maximum.
<b>Plating</b>	See Appendix-A for information about the plating of steel spring nuts.

Tinnerman® is a registered trademark of Trans Technology Engineered Components, LLC, Eaton Yale & Towne Inc.. Kanebridge's spring nuts are not manufactured by or connected with the producers of Tinnerman® nuts.